

The FastFire RD (Rifle Dot) sight features a bright red dot for fast target acquisition and easy aiming. The 1x magnification and 2 MOA red dot allow both-eyes-open shooting for enhanced awareness. The FastFire RD has unlimited eye relief.



Mounting the Optic

The FastFire RD comes factory-ready to mount to a Picatinny rail system. Using the supplied hex wrench, loosen the screw on the right side of the base to open the mount just enough to fit over the width of the rail. Once positioned on the rail, test for proper eye relief and use the wrench to tighten the base screw to 45 in-lbs.

Battery Installation / Replacement

This sight is powered by a single AAA battery. The battery compartment is located on the front of the sight. To open the compartment, turn the cap counterclockwise. Insert the battery with the positive side (+) first and re-tighten cap completely. To preserve battery life, the FastFire RD is equipped with an Auto-Shut Off. The sight automatically turns off after 4 hours on the 4 brightest settings and 8 hours on the 3 night vision settings. During extended storage, it is recommended that you remove the battery.

Red Dot Illumination Adjustment

To turn the red dot on, press any button on the top of the sight. Once the dot is illuminated, the forward and back buttons can be used to select any of the 7 brightness settings. To turn the sight off, press and hold the rear button on top of the sight for 4 seconds.

Windage / Elevation Adjustment

The elevation adjustment screw is located on top of the sight and the windage adjustment screw can be found on right side. Use a small screwdriver to adjust bullet placement up or down and left or right. Arrows on the dial indicate direction of movement. Each click represents 0.5 MOA of adjustment with 110 MOA overall travel for windage and elevation.

WARRANTY



We will repair or replace your Burris optic if it is damaged or defective. The warranty is automatically transferred to future owners.

- No repair or replacement charge
 - No warranty card needed
 - No receipt needed
 - No questions asked

FASTFIRE RD[™] SPECIFICATIONS

| Item # | 300260 |
|---|-----------------|
| Clear Objective Diameter | 23 mm |
| Dot Size | 2 MOA |
| Dot Color | Red |
| Finish | Matte |
| Mount | Picatinny Mount |
| Eye Relief | Infinite |
| Click Value | 0.5 MOA |
| Elevation Adjustment, Total Capability | 110 MOA |
| Windage Adjustment, Total Capability | 110 MOA |
| Length | 2.8 in. |
| Weight | 6.4 oz. |
| Battery | AAA |





Burris Company

331 East 8th St. • Greeley, CO 80631 (970) 356-1670 BurrisOptics.com Facebook.com/BurrisOptics

INSTR-9514